

Application Serial No: 10/748,922
In reply to Office Action of 25 August 2005

Attorney Docket No. 84480

AMENDMENTS TO THE CLAIMS

1. (currently amended) A method of switching a binary digital signal having a discrete power level from a single input optical fiber to at least one output fiber comprising the steps of:

providing an input signal into an input optical fiber;

splitting said input signal ~~to form a plurality of~~ repeatedly
in a binary fashion N times to produce 2^N split input
signals;

selectively amplifying at least one of said ~~plurality of said~~
 2^N split input signals with an amplifier; and

attenuating each of said ~~plurality of said~~ 2^N split input
signals after said step of selectively amplifying.

2. (canceled)

3. (original) The method of claim 1 wherein said selectively amplifying is accomplished through the use of a semiconductor optical amplifier.

Application Serial No: 10/748,922
In reply to Office Action of 25 August 2005

Attorney Docket No. 84480

4. (original) The method of claim 1 wherein said selectively amplifying is accomplished through the use of an erbium doped optical fiber pumped by a laser.
5. (original) The method of claim 1 wherein said selectively amplifying is accomplished through the use of a controller.
6. (currently amended) The method of claim 1 wherein attenuating each of said ~~plurality of said~~ 2^N split input signals comprises filtering said split input signals.
7. (currently amended) The method of claim 1 wherein attenuating each of said ~~plurality of said~~ 2^N split input signals comprises the step of passing said split input signals through a partially opaque section of fiber.
8. (currently amended) A fiber optic switch comprising:

an input optical fiber capable of transmitting an input
signal;

at least one splitter joined to said input optical fiber for
splitting said input optical fiber ~~to form a plurality~~
of said at least one splitter arranged in a binary

Application Serial No: 10/748,922
In reply to Office Action of 25 August 2005

Attorney Docket No. 84480

fashion N times to produce 2^N split optical fibers, each
of said split optical fibers being capable of carrying
said input signal;

at least one amplifier joined to each of said ~~plurality of~~
~~said 2^N split optical fibers, each amplifier being~~
controllable to amplify the signal in the joined one of
the split optical fibers; and

at least one attenuator joined to each amplifier to attenuate
the signal in each of said ~~plurality of said 2^N split~~
optical fibers.

9. (canceled)

10. (original) The switch of claim 8 wherein said at least one
amplifier is a semiconductor optical amplifier.

11. (original) The switch of claim 8 wherein said at least one
amplifier is an erbium doped optical fiber pumped by a laser.

12. (original) The switch of claim 8 further comprising a
controller joined to said at least one amplifier for selectively
controlling the joined amplifier.

Application Serial No: 10/748,922
In reply to Office Action of 25 August 2005

Attorney Docket No. 84480

13. (original) The switch of claim 8 wherein said at least one attenuator is an optical filter.

14. (original) The switch of claim 8 wherein said at least one attenuator a partially opaque section of fiber.

15. (new) A method of switching a binary digital signal having one of two discrete power levels representing 0 and 1 from a single input optical fiber to at least one output fiber comprising the steps of:

providing an input signal, having a signal to noise ratio,
into an input optical fiber;

splitting said input signal repeatedly in a binary fashion N
times to produce 2^N split input signals;

selectively amplifying at least one of said 2^N split input
signals by a magnitude equal to the signal to noise
ratio of said input signal through the use of a laser
activated amplifier comprised of an erbium doped optical
fiber pumped by a laser; and

Application Serial No: 10/748,922
In reply to Office Action of 25 August 2005

Attorney Docket No. 84480

attenuating each of said 2^N split input signals by an amount identical to the amount amplified by said laser activated amplifier after said step of selectively amplifying said at least one of said 2^N split input signals, such that each of said 2^N input signals that were not first amplified are now attenuated to a power level of 0.

16. (new) The method of claim 15 wherein the step of selectively amplifying at least one of said 2^N split input signals with a laser activated amplifier comprised of an erbium doped optical fiber pumped by a laser, comprises amplifying said at least one of said 2^N input signals by a magnitude greater than the signal to noise ratio of said input signal

17. (new) The method of claim 15 further comprising the step of delivering a control signal to said laser activated amplifier by means of a controller to amplify said at least one of said 2^N input signals.

18. (new) The method of claim 17 further comprising the steps of establishing said two discrete power levels at 0 mw to 1 mw representing a 0 and at 3 mw to 4 mw representing a 1.

Application Serial No: 10/748,922
In reply to Office Action of 25 August 2005

Attorney Docket No. 84480

19. (new) The method of claim 18 wherein the step of selectively amplifying at least one of said plurality of said 2^N split input signals with a laser activated amplifier comprising an erbium doped optical fiber pumped by a laser, further comprises amplifying said at least one of said 2^N input signals by a factor of 10.

20. (new) The method of claim 19 wherein the step of attenuating each of said 2^N split input signals by an amount identical to the amount amplified by said laser activated amplifier after said step of selectively amplifying said at least one of said 2^N input signals further comprises attenuating each of said split input signals by a factor of 10.